

EXXHAUST

Light weight and very flexible exhaust hose of TPE-coated Polyester fabric

Applications	exhaust gas extraction, extraction systems, automotive engineering, vehicle construction, air extraction
Structure	TPE coated polyester fabric, black / jet black (similar RAL 9005), profile helix / hollow profile helix
Temperature	-40°C up to 200°C *with proper exhaust gas routing and sufficient fresh air supply (approx. 50%).
Properties	very good flexibility, very good temperature resistance, with outer wearstrip profile, good oil & petrol resistance, good tensile strength crush-resistant can be driven over



hydrolysis
resistant



microbe-
resistant



high
temperature



air



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	68,00	0,40	48	0,40	1,65	5	29605051-0500-000-77
51	68,00	0,40	48	0,40	2,47	7,5	29605051-0750-000-77
51	68,00	0,40	48	0,40	4,95	15	29605051-1500-000-77
51	68,00	0,40	48	0,40	3,80	10	29605051-1000-000-77
63	80,00	0,40	53	0,28	2,03	5	29605063-0500-000-77
63	80,00	0,40	53	0,28	4,80	10	29605063-1000-000-77
63	80,00	0,40	53	0,28	3,04	7,5	29605063-0750-000-77
63	80,00	0,40	53	0,28	6,09	15	29605063-1500-000-77
76	93,00	0,40	60	0,17	3,66	7,5	29605076-0750-000-77
76	93,00	0,40	60	0,17	7,32	15	29605076-1500-000-77
76	93,00	0,40	60	0,17	5,40	10	29605076-1000-000-77
76	93,00	0,40	60	0,17	2,44	5	29605076-0500-000-77
102	119,00	0,40	71	0,05	3,27	5	29605102-0500-000-77
102	119,00	0,40	71	0,05	4,90	7,5	29605102-0750-000-77
102	119,00	0,40	71	0,05	9,80	15	29605102-1500-000-77
102	119,00	0,40	71	0,05	13,07	20	29605102-2000-000-77
102	119,00	0,40	71	0,05	7,10	10	29605102-1000-000-77
127	144,00	0,40	100	0,04	8,70	10	29605127-1000-000-77
127	144,00	0,40	100	0,04	4,06	5	29605127-0500-000-77
127	144,00	0,40	100	0,04	6,09	7,5	29605127-0750-000-77
127	144,00	0,40	100	0,04	12,19	15	29605127-1500-000-77
152	169,00	0,40	110	0,03	14,57	15	29605152-1500-000-77

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
152	169,00	0,40	110	0,03	10,40	10	29605152-1000-000-77
152	169,00	0,40	110	0,03	4,86	5	29605152-0500-000-77
152	169,00	0,40	110	0,03	7,29	7,5	29605152-0750-000-77
203	220,00	0,40	155	0,01	6,48	5	29605203-0500-000-77
203	220,00	0,40	155	0,01	9,72	7,5	29605203-0750-000-77
203	220,00	0,40	155	0,01	13,70	10	29605203-1000-000-77
203	220,00	0,40	155	0,01	19,44	15	29605203-1500-000-77