


FLEXADUX® HT 650 CL

Highly flexible clip hose for temperatures up to +650°C

Applications	exhaust gas extraction, extraction systems, high temperature applications, automotive engineering, automation technology & robotics
Structure	coated fabrics / silicone coated glass fabric, grey / silver grey (similar RAL 7001), opaque, clip profile / multi-layer
Temperature	-60°C up to 650°C
Properties	excellent flexibility, excellent temperature resistance, with external abrasion protection spiral, flame-retardant
Norms	flame-retardant according to UL 94 fire protection standard / V0



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
60	70,00	0,75	36	0,31	5,93	6	04200060-0600-000-00
60	70,00	0,75	36	0,31	2,96	3	04200060-0300-000-00
76	86,00	0,75	45	0,20	3,75	3	04200076-0300-000-00
76	86,00	0,75	45	0,20	7,51	6	04200076-0600-000-00
80	90,00	0,75	48	0,17	3,95	3	04200080-0300-000-00
80	90,00	0,75	48	0,17	7,90	6	04200080-0600-000-00
102	112,00	0,75	60	0,11	2,58	3	04200102-0300-000-00
102	112,00	0,75	60	0,11	5,16	6	04200102-0600-000-00
112	122,00	0,75	66	0,09	3,45	3	04200112-0300-000-00
112	122,00	0,75	66	0,09	6,91	6	04200112-0600-000-00
120	130,00	0,75	72	0,08	3,71	3	04200120-0300-000-00
120	130,00	0,75	72	0,08	7,42	6	04200120-0600-000-00
127	137,00	0,75	75	0,07	3,92	3	04200127-0300-000-00
127	137,00	0,75	75	0,07	7,85	6	04200127-0600-000-00
152	162,00	0,75	90	0,05	4,70	3	04200152-0300-000-00
152	162,00	0,75	90	0,05	9,39	6	04200152-0600-000-00
160	170,00	0,75	96	0,04	4,94	3	04200160-0300-000-00
160	170,00	0,75	96	0,04	9,87	6	04200160-0600-000-00
203	213,00	0,75	120	0,03	6,27	3	04200203-0300-000-00
203	213,00	0,75	120	0,03	12,54	6	04200203-0600-000-00
228	238,00	0,75	158	0,02	4,78	3	04200228-0300-000-00
228	238,00	0,75	158	0,02	9,56	6	04200228-0600-000-00

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
254	264,00	0,75	175	0,02	7,81	3	04200254-0300-000-00
254	264,00	0,75	175	0,02	15,62	6	04200254-0600-000-00
305	315,00	0,75	210	0,01	9,41	3	04200305-0300-000-00
305	315,00	0,75	210	0,01	18,83	6	04200305-0600-000-00
356	366,00	0,75	245	0,01	7,39	3	04200356-0300-000-00
356	366,00	0,75	245	0,01	14,77	6	04200356-0600-000-00
407	417,00	0,75	280	0,01	25,06	6	04200407-0600-000-00
407	417,00	0,75	280	0,01	12,53	3	04200407-0300-000-00
457	467,00	0,75	360	0,01	9,45	3	04200457-0300-000-00
457	467,00	0,75	360	0,01	18,89	6	04200457-0600-000-00
508	518,00	0,75	400	0,01	15,65	3	04200508-0300-000-00
508	518,00	0,75	400	0,01	31,30	6	04200508-0600-000-00